

# Workstation for document reading Regula 70X9



Full page passport reader with no moving parts inside.

Automatic reading and authenticity verification of passports, IDs, visas, driver's licenses and other identification documents.

Optical character recognition, reading of barcodes, RFID and SmartCard chips.

Full data processing onboard with a built-in PC.



A small-sized compact reader for desktop use. The body is made of hard plastic. Full data processing onboard with a built-in PC. Video output for connection to an external monitor. Four USB ports for connection of external devices. LAN connection. No moving parts. Reliable, convenient and easy-to-use.

The device allows capturing images in white, infrared, ultraviolet and coaxial lights. Certain models are equipped with modules for reading RFID chips and smart cards. The device is supplied with software development kit (SDK) for easy integration into existing end-user systems.

Reader Regula 70X9 can be optionally equipped with a built-in USB Multi Touch Monitor.

### **Functionality**

- · Capturing and processing images
  - · supported document formats
    - ID-1
    - ID-2
    - ID-3
    - other documents with maximum size 88×128 mm
  - automatic detection of a document in a scanning zone
  - o automatic scanning after document detection
  - o elimination of glare from laminate and holograms in white and IR light
  - compensation of external light hitting during image capture in ultraviolet light (Smart UV)
  - automatic selection of UV illumination intensity according to the document type
  - · search and cropping of a document image from a general image
- The MRZ detection and recognition
- Recognition and reading of 1D and 2D barcodes
- · Automatic recognition of a document type
- Processing graphic fields
- OCR of the visual zone
- Reading RFID tags
- · Analyzing and comparing text data
- · Automatic authenticity verification of a document

#### Operation

- 1. The optical reader automatically detects a document in the scanning area of the device.
- 2. Document images are captured in different illumination modes. At the same time data is read from RFID tags and smart cards.
- 3. Regula Document Reader SDK processes data.
- 4. Results of the verification are ready for further use.

### **Application**

- · Border control services
- Aviation security services
- Law-enforcement agencies
- · Immigration services
- Financial institutions
- Hotels
- Car rental and leasing companies
- Cellular companies
- · Business centers security service
- Event-agencies
- Medical institutions
- Tourist agencies



- Ticket offices
- Visa support agencies and consulates
- Insurance companies
- · Casino security service

#### **Additional functions**

- Video output for connection to an external monitor
- Four USB ports for connection of external devices
- LAN connection
- Programmable indicators of the device status:
  - multicolour LED indicator red, yellow, green
  - buzzer

### **Delivery Set**

- Regula Document Reader SDK
- Windows 10



WORKSTATION FOR DOCUMENT READING REGULA		Model						
		7029.111-5A	7039.111-5A	7029.111-5	7039.111-5	7029.111-18	7039.111-18	
Optical re	eader							
Light sources	White	+	+	+	+	+	+	
	Infrared 870 nm	+	+	+	+	+	+	
	Infrared 950 nm	optionally	optionally	optionally	optionally	optionally	optionally	
	Ultraviolet 365 nm	+	+	+	+	+	+	
	Coaxial white	+	+	+	+	+	+	
Camera se	ensor, megapixels	5			8			
Image res	olution, ppi	470 :	± 5%	500 :	± 5%	860 ± 10%		
Frame size	e, pixels		2592>	×1944		4908	×3684	
Scanning	area, mm			ا 88×128 – full	passport page			
Video sens	sor type			CM	IOS			
Color mod	el	RGB						
Color dept	h, bit	24						
RFID Reader (details)		+	+	+	+	+	+	
Til ID Hea	idei ( <u>details)</u>	т	-	-	т	т	т	
Smart Ca	rd Reader (details)		+		+		+	
Built-in P	C (details)	+	+	+	+	+	+	
Technica	I Specifications							
Scratch re	sistant glass	optionally						
Dimension	ıs (L×W×H), mm	179×160×13 5	190×160×13 5	179×160×13 5	190×160×13 5	179×160×13 5	190×160×13 5	
Weight, kg	g, max	1.5						
Power sup	oply from USB port, V	19						
Certificat	es							
CE		+	+	+	+	+	+	
Climatic (	Conditions							
Relative a	ir humidity	3585% (non-condensing)						
Air temperature, °C		+5+40						
IP rating				IP	20			

RFID Reader	
Standards supported	ISO 14443: type A and B
Data exchange rate, Kbaud	106, 212, 424, 848
RFID tag positioning	RFID reading regardless of tag position in the document
Anti-collision	reading an RFID tag according to the MRZ



Smart Card Reader				
Standards supported	ISO/IEC 7816-1, -2, -3, -4; EMV2000 4.1, Level 1			
Data exchange rate, Kbaud	2–500			
Smart card type	asynchronous, $T = 0$ and $T = 1$			

Built-in PC				
CPU	Intel® Core™ with active fan heatsink			
RAM	at least 8 GB			
SSD	at least 120 GB			
HDMI	+			
Network connection	Intel 10/100/1000			
USB 2.0 ports	2			
USB 3.0 ports	2			



## Document reader software development kit (SDK)

SDK (Full) consists of three modules:

- Basic supplied together with a device by default
- VizOCR reading textual fields from a document page
- AAC automatic authenticity control

VizOCR and AAC modules are optional and used to extend the functionality of Basic module.

Updates for SDK are provided regularly. Basic module has unlimited support. VizOCR and AAC are updated on subscription basis.

Functionality		Full SDK modules		
		Basi c(supplied by default)	VizOCR	AAC
Doc	ument image capture and processing			
Document formats	<ul> <li>ID-1 (identity card)</li> <li>ID-2 (passport card, visa)</li> <li>ID-3 (passport)</li> <li>other document formats up to 88×128 mm</li> </ul>	+		
Scanning process	<ul> <li>document detection sensor</li> <li>automatic scanning after document detection</li> <li>elimination of glare from laminate and holograms for white and infrared illumination</li> <li>compensation of external light hitting during image capture in UV light (Smart UV)</li> <li>automatic intensity selection of UV illumination for a certain document type</li> <li>search and cropping of a document image from a received image</li> </ul>	+		
	Machine readable zone (MRZ)			
Supported MRZ formats	<ul> <li>in conformity with ICAO 9303:</li> <li>44×2</li> <li>30×3</li> <li>36×2</li> <li>in conformity with ISO IEC 18013 (IDL):</li> <li>30×1</li> <li>support of special MRZ data structure for documents of certain countries</li> </ul>	+		
Features	<ul> <li>search for the MRZ along the whole document image</li> <li>MRZ recognition in infrared and white light</li> <li>control of check digits and data structure in conformity with the requirements of ICAO 9303 and BSI TR-03105 Part 5.1</li> <li>evaluation of MRZ quality specifications in conformity with ICAO 9303, ISO 7501, 1831, 1073-2 standards</li> </ul>	+		
Barcodes				
Supported formats	<ul> <li>1D: Codabar, Code39 (+extended), Code93, Code128, EAN-8, EAN-13, IATA 2 of 5 (Airline),</li> </ul>	+		



	Interleaved 2 of 5 (ITF), Matrix 2 of 5, STF (Industrial), UPC-A, UPC-E  • 2D: PDF417, Aztec Code, QR Code, Datamatrix			
Authentication	barcode format check			+
Αι				
Order of document type recognition	<ul> <li>Country→Type→Series</li> </ul>		+	+
Features	<ul> <li>receiving a document template from the SDK database containing the following information:         <ul> <li>text and graphic fields position</li> <li>availability of barcodes and security features</li> <li>authenticity verification and its parameters</li> <li>RFID-chip availability</li> <li>a reference image from Information Reference Systems «Passport», «Autodocs», «Frontline Documents System»</li> </ul> </li> <li>processing of the received document images in compliance with the sample, including document image rotation by the angle given in the sample</li> </ul>		+	+
	Graphic fields processing			
Types of graphic fields	<ul> <li>portrait of the document holder</li> <li>signature</li> <li>barcode</li> <li>fingerprint, etc.</li> </ul>	+		
Features	<ul> <li>cropping and displaying graphic fields as separate images in compliance with the sample of the corresponding document</li> <li>automatic searching of faces on the document image and cropping the document holder portrait if the document type is not recognized</li> <li>document image rotation according to the document holder portrait position</li> </ul>	+		
	OCR of the visual zone			
Recognition of character sets	<ul> <li>Central European and Eastern European Latin (1250)</li> <li>Cyrillic (1251)</li> <li>Western European Latin (1252)</li> <li>Greek (1253)</li> <li>Turkish (1254)</li> <li>Baltic (1257)</li> <li>other fonts of any size</li> </ul>		+	
Features	<ul> <li>dictionary support (name, surname, address, country, etc.)</li> <li>automatic text division into separate fields (e.g. dividing the address into postal code, country, state, etc.)</li> <li>recognition of dates with complex formats</li> <li>recognition of characters from different character sets in one line</li> </ul>		+	
	RFID SDK			
Supported RFID-chip standards	<ul> <li>ISO/IEC 14443-2 (type A and B)</li> <li>ISO/IEC 14443-3 (MIFARE® Classic Protocol)</li> <li>ISO/IEC 14443-4</li> </ul>	+		
Data access modes	• Direct	+		



	<ul><li>BAC</li><li>EAC</li><li>PACE</li><li>SAC</li></ul>		
Authentication	<ul> <li>active (AA)</li> <li>passive (PA)</li> <li>chip (CA v1, CA v2)</li> <li>terminal (TA v1, TA v2)</li> </ul>	+	
Supported applications	<ul> <li>ePassport (DG1-DG16)</li> <li>eID (DG1-DG21)</li> <li>eSign</li> <li>eDL (DG1-DG14)</li> </ul>	+	
Certificate management	<ul> <li>local storage</li> <li>receiving certificates online through the program interface</li> <li>Master List, CRL support</li> </ul>	+	
Features	<ul> <li>reading RFID chips with extended length support</li> <li>reading RFID chips in compliance with ICAO LDS 1.8, PKI 1.1 data formats</li> <li>certified by BSI TR-03105 Part 5.1, BSI TR-03105 Part 5.2</li> </ul>	+	
A	nalysis and comparison of text data		
Document areas for cross-checking of the readout data	<ul> <li>MRZ</li> <li>VIZ</li> <li>RFID-chip</li> <li>barcode</li> <li>contact chip (Smart Card)</li> </ul>	+	
Verification	<ul> <li>validity of any dates</li> <li>authenticity of names and surnames according to lists of wordstops</li> <li>zero numbers of sample documents</li> </ul>	+	
Adjustment of formats and measuring units to those used in the user OS	<ul><li>date</li><li>weight</li><li>height, etc.</li></ul>	+	
Features	<ul> <li>complete or partial comparison of fields</li> <li>integration of data received from several document pages</li> <li>calculated field support (age, etc.)</li> <li>transliteration to Latin characters in compliance with ICAO 9303 standards for comparison with the MRZ</li> </ul>	+	
	Authenticity verification		
Operation available for any document	<ul> <li>checking luminescence (UV Dull Paper) of:         <ul> <li>the form</li> <li>the MRZ area</li> <li>the portrait area</li> </ul> </li> <li>checking the MRZ print contrast in compliance with ICAO 9303 (IR B900 lnk)</li> </ul>	+	
Operations available after document type recognition	<ul> <li>checking image patterns in white, IR and UV light</li> <li>checking luminescence of UV protection fibers</li> <li>detection of false luminescence</li> <li>checking photo embedding type: printing or attachment</li> <li>checking IR Visibility of:</li> </ul>		+



	<ul> <li>elements of the form</li> <li>text data</li> <li>the photograph (main and additional)</li> </ul> <li>detection of holograms (OVD), OVI</li> <li>reading a luminescent text and comparing it with the data obtained from the MRZ and VIZ (OCR Security Text)</li> <li>visualization of IPI (Invisible Personal Information)</li> <li>checking retroreflective protection</li> <li>checking barcode format</li>		
Features	<ul> <li>checking operations are adjusted to documents with different degrees of wear and tear</li> <li>the choice of checking operations depends on security features available in a questioned document</li> </ul>		+
	Additional SDK functions		
Image formats	<ul> <li>.BMP</li> <li>.JPG</li> <li>.JP2</li> <li>.PNG</li> <li>.TIF</li> <li>other image formats are possible on request</li> </ul>	+	
Interoperability	<ul> <li>comparison modules:         <ul> <li>fingerprint images from RFID chip and externalfingerprint scanner</li> <li>face images from document data page and/or RFID chip</li> </ul> </li> <li>Information Reference Systems «<u>Passport</u>», «<u>Autodocs</u>», «<u>Frontline Documents System</u>»</li> </ul>	*	
OS compatibility	<ul> <li>Windows 7 (x86, x64), Windows 8, Windows 10, Windows 11, Ubuntu 20.04—24.04, Debian 11—12, RHEL 9, macOS 11+</li> </ul>	+	
Drivers	Microsoft certified	+	
Features	<ul> <li>simultaneous optical scanning and RFID chip reading</li> <li>firmware upgrade via USB interface (automatic upgrade after installing new SDK version)</li> <li>multilingual interface</li> </ul>	+	
	Software updates		
SDK	• twice a year	*	
Document template database	• monthly	*	

<sup>\* -</sup> on request / individual agreement



# Visual zone








**RFID-chip (Radio-frequency identification)** 




Document data readout: textual data readout

# Visual zone





# **RFID-chip (Radio-frequency identification)**



Document data readout: graphic data readout



## **White**



Performed security checks in white light

White IR



Performed security checks in infrared light



## UV



Performed security checks in ultraviolet light



Checking photo embedding type: printing or attachment





Checking the blank of the document



Checking the personal data



Viewing the passport from IRS database



MRZ of the passport





### Visual zone of the passport



RFID-chip of the passport




Text data comparison of the passport




Graphic data comparison of the passport





Security features of the passport



Security features of the passport